

Automatic Calculation & Positioning Curtain Pleat Sewing



Data input can be performed easily by a new type color liquid crystal panel.

This machine equipped with "Pattern Match Sewing".

Automatic Operation Beautiful & Exact Pleating Compact Design

☆Simple Operation

The operational function has been improved more than a conventional machine.



Except the first and the last material set, sewing is possible without holding.

The width adjustment which will be performed if the remaining pleats are 3 was fully automated. Original width measurements and the data input for next product can be performed in advance even during operation, it enables improving machine operating rate.

Special cloth control roller and cloth feed device ensure rapid and effective cloth control, the cycle time to 1 pleat does not change.

One operator can use 2 stations. Tasks such as hooking, picking threads, and folding can be efficiently performed even with 1 station.

Model Name	NCT-250ENC / SA-3		
Number of Fold	1 fold	2 fold	3 fold
Necessary Pleat Width	25 ~ 70	46 ~ 130	60 ~ 165
Hook Distance	125 - 235 100 - 220	115 - 230 70 - 190	105 - 225 55 - 170
Machine Head	AMS210EN Max. Sewing Speed 2800rpm		
Voltage and Electric Power	3-phase 200V : 550W		
Air Pressure / Power Consumption	5kgf/cm2 1HP(option)		
Dimensions	1350mm(w) x 1200mm(d) x 1130mm(h)		

*Specifications and appearance are subject to change without prior notice for improvement.

Manufacture & Sales

NAKANIHON-JUKI CO.,LTD Head Office: 3-33 Kamiishikawa-cho, Nakamura-ku, Nagoya 453-0835, Japan mail: honsha@nakanihon-juki.co.jp Inquiries

Feb, 2014 Printed in Japan(C)