

For manufacture of order-made curtains

Automatic operation, automatic width adjustment

NCT-250E/SA3

Automatic curtain pleat sewing device

Now 20% more efficient than conventional types!
Sharp, clean initial stitching!

Hands-free automatic operation

Beautiful, accurate stitching

Compact design



Features

Totally hands-free automatic operation, except for first and last set.

Width adjustment is also completely automated for final three tucks.

Former width measurements and data for next product can be input in advance even during operation, improving machine operating rate.

Special cloth control roller and cloth feed device ensure rapid and effective cloth control, to accurately follow planned cycle time per pleat.

One operator can use 2 stations. Tasks such as hooking, picking threads, and folding can be efficiently performed even with 1 station.

Specification

Model No.	NCT-250E/SA3
Hook interval	70mm ~ 230mm (may vary under some conditions)
Cloth length required for pleat	Single fold 24mm ~ 50mm
	Double fold 40mm ~ 140mm
	Triple fold 65m ~ 180mm
Pleat height	12mm ~ 40mm
Sewing machine used	AMS210EN(max. rotation 2800 rpm)
Voltage / Power supply	Single phase 100V / 3-phase 200V : 500W
Air pressure / Power consumption	5kgf/cm ² 1.0HP (option)
Installed dimensions	1200mm(w)×1200mm(d)×1130mm (h)

*Specifications and appearance may vary without notice as improvements are made.
The listed contents of this catalog are current as of November 2009.

Manufacture & Sales



NAKANIHON-JUKI CO.,LTD

Head Office: 3-33 Kamiishikawa-cho,
Nakamura-ku, Nagoya, 453-0835, Japan
Phone: 052-412-1211 (switchboard)

Inquiries